



	NTSC	PAL
Image system		
Lens	1/4" SONY Exview HAD CCD	
Optical zoom	F1.6 - F4.5	
Focal length	f=3.4 mm (wide) to 122.4 mm (tele)	
View Angle	57.8°(wide end) to 1.7°(tele end)	
Minimum Working Distance	320mm(wide end) to 1500mm(tele end)	
Effective pixels(HxV)	380K pixels approx.	440K pixels approx.
Scanning system	2:1 Interlace V: 59.94Hz, H: 15.734KHz	2:1 Interlace, V: 50Hz, H: 15.625KHz
Sync system	Internal / line-lock	
Video output	1Vpp composite output, 75 ohm	
Horizontal resolution	560 TV Lines	
S/N ratio	More than 50 dB	
Zoom limit	UP TO 432X (optical 36X, digital 12X)	
Focusing system	Auto(normal sensitivity / low sensitivity)	
Focus	Auto (sensitivity: normal, low), One-push AF: Manual, Infinity, Interval AF, Zoom Trigger AF	
Minimum illumination	Normal mode: 0.07 lux (F1.6, 1/60(1/50)sec. ICR OFF, 10 IRE) Slow shutter mode: 0.005 lux (F1.6, 1/4(1/3)sec. ICR OFF, 10 IRE) Night mode: 0.0075 lux (F1.6, 1/60(1/50)sec. ICR ON, 10 IRE) Slow shutter mode: 0.0005 lux (F1.6, 1/4(1/3)sec. ICR ON, 10 IRE)	
Gain control	Auto	
White balance	Auto, ATW, One-push	
Electric shutter	1/1 to 1/10,000sec. 22 Steps	
Auto slow shutter	On / Off	
AE control	Auto, Manual, Priority mode, Bright, EV compensation, Back-light compensation	
EV compensation	-10.5→+10.5dB(1.5dB steps)	
Backlight Compensation	On / off	
Alarm function	Yes	
Day/Night mode	Auto / manual	
Flickerless	Yes	
Wide dynamic	YES	
Picture Effect		
Mirror Image	Yes	
P/T Operation		
Pan Range	360° continuous	
Tilt range	92°	
Manual Pan speed	0.1 - 90°/s	
Manual Pan speed (turbo)	0.1°/s: max dig. zoom : 0.4°/s: max opt. zoom	
Manual tilt speed	150°/sec	
Manual tilt speed (turbo)	0.1 - 45°/s	
Manual tilt speed (turbo)	0.1°/s: max dig. zoom : 0.4°/s: max opt. zoom	
Preset speed	Pan: 430°/sec(max); Tilt: 200°/sec (max)	
Proportional P/T	Provided	
Pan/Tilt limit	user definable	
Auto Flip	on/off	
Zoom Limit	x36,x72,x144,x288,x432	
Programmable Preset	253 points	
Programmable Tours	4 pattern tours memorizing up to 8 mins of manual control	
Privacy zone	On / off, up to 24 zones (3D Privacy Zone)	
Scan function	Random, frame and auto-scan selectable	
Alarm	6 inputs / 1 output	
Preset titles	Max 20 characters	
Password protection	alphanumerical Dome OSD setup protection	
Other Superior Functions	Super Fine Pan for 0.02° Accuracy / Motion Detection / Scheduling	
Remote control		
Remote control	MESSOA P/D (Also support Pelco-P/D, GE, Bosch, Erntec, Tyco)	
Special Commands	support absolute(X, Y, Z) position	
Interface	RS485	
Baud Rate	2400,4800,9600,19200 bits(DIP-sw selectable)	
OSD		
Multi language support	English, Simplified Chinese, Traditional Chinese, Spanish, Portuguese, French, Japanese, Germany, Polish, Italian	
NETWORK & Digital Video		
Video Compression		
Compression	H.264/MPEG-4/Motion-JPEG	
Picture Resolution	Full D1 (720x480 in NTSC, 720x576 in PAL) CIF (352x240 in NTSC, 352x288 in PAL) QCIF (160x112 in NTSC, 176x144 in PAL)	
Bit Rate	28K - 3M bps	
Image Frame Rate	30fps at full D1 resolution (NTSC) 25fps at full D1 resolution (PAL)	
Multi-stream	Up to 4 configurable frame rate /bit rates streams for preview and recording	
Network		
LAN port	Ethernet(10/100 Base-T)	
WAN port	Ethernet(10/101 Base-T)	
Software		
Web browser	Microsoft Internet Explorer 6.0 or above	
SDK	ActiveX control, C SDK	
Security	Password Protection: Configured by the Administrator	
Mechanical/Environment		
Operating temperature	-40 °C - 60 °C (-40°F -140°F)	
Operating humidity	20% - 80% RH	
Storage temperature	-20 °C - 60 °C (-4°F-140°F)	
Dimensions(øxH)	216.6mm X 324.0mm (85.3" * 12.8") (height)	
Weight	3800g (8.14 lb) approx.	
Electrical		
Power requirement	AC24V +/-10%	
Power consumption	52.5W (max.)	
Regulation	750KG (1653 lb) impact resistance	
Vandal proof	IP67 (With Heater and Blower)	
Water proof	IP67 (With Heater and Blower)	
Applications (Optional)	Pendant Pipe Mount (SAD702) / Simple Wall Mount (SAD703) / Wall Mount with Power Box (SAD704) / Pendant Pipe Mount with Power Box(SAD705) / Parapet Wall Mount (SAD706) / Corner Mount(SAD707) / Pole Adaptor (SAD708) / Pipe Extension Bracket(SAD709) / Sun Shield(SAD710)	
Ordering information	NIC950PRO-HN2-US (US Power Cord)	NIC950PRO-HP2-EU (EU Power Cord)
		NIC950PRO-HP2 -UK (UK Power Cord)
		(UK)